


Dishwashing
ADVANCE Series - Pass-through
DISHWASHER, AD-120 C

DIMENSIONS				PASS-THROUGH DISHWASHER, AD-120 C		
Length	mm	675,00	730,00	Made of stainless steel.		
Depth	mm	675,00	750,00	Double skinned with insulation for improved soundproofing and reduced loss of heat inside the machine.		
Height	mm	1.400,00	1.600,00	Hourly production: 1,200 dishes/hour.		
Weight	Kg	118,00	134,00	Maximum diameter of dishes: Ø 42 cm.		
Volumen	m3	0,64	0,88	Valid for self-service trays.		
ELECTRICITY				Electronic operation.		
Electric power	KW	17,79		Wash cycles: 55"-80"-120", continuous washing program and stand-by temperature.		
230V - 1+N		2x25+T - 100 A		Double rotating wash and rinse systems, above and below.		
230V - III		3x10+T - 63 A		Heating elements in tank and boiler.		
400V - III+N		4x6+T - 40 A		Two independent wash pumps for lower and upper systems, 590 W each.		
WATER				Tank with 4.5 kW heating element.		
Water consumption (lit/h)		60,00		Tank capacity: 45 litres.		
Pressure (Kg/cm2)		2 - 4		Boiler with 12 KW heating element.		
GAS				Water consumption: 3.5 litres/rinse.		
Not used				Thermostatic temperature control: washing at 60°C and rinsing at 90°C.		
				Thermo stop system that guarantees minimum rinsing temperature of 85°C.		
				Digital wash and rinse temperature display.		
				Security thermostats.		
				Self diagnostic system.		
				Anti - return protection system.		
				Built-in automatic rinse dispenser.		
				Equipped with detergent dispenser.		
				Drain pump and drainage cycle.		
STEAM				Safety switch for hood opening.		
				Adjustable legs.		
AIR				Baskets equipment: 1 x CT-10, 2 x CP-16/18 and 8 cutlery containers.		
				Power: 17.79 KW		
				Dimensions: 675 x 675 x 1400 mm.		
LEVEL SOUND				68,50		
Certificate EQNET- CE				SGS-2199-0192-1		

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	275	525	580		Prever Interruptor diferencial
SOFT COLD WATER	90	515	260	3/4"	Prever llave de corte en la toma
DRAIN	545	480	260	30x25	

