



Datasheet

Project:

Quantity:

Model #:

Approval:

For Commercial Use Only

UC-48R 48" Undercounter Work Top Refrigerator - 12 Cu. Ft.



FEATURES

- Stainless steel exterior and interior
- Refrigeration system keeps food at safe temperatures
- Self-closing doors with 90 degree stay-open feature
- Adjustable heavy-duty PVC coated shelves
- Recessed door handle
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Removable installation board
- Hydro-Carbon R290 refrigerant
- 4" backsplash optional

This Coldline commercial undercounter refrigerator is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
- ETL Sanitation Listed

Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



USR Brands, Inc.

Phone: 800-764-1172 | www.usrbrands.com | sales@usrbrands.com

Rev. 09-2021

Page 171

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	47.2"W x 29.5"D x 35.5"H
Low Profile Dimensions	47.2"W x 29.5"D x 34"H
Interior Dimensions	42.5"W x 22.9"D x 23.5"H
Packaging Dimensions	50"W x 32.3"D x 38.5"H
Working Height	35.3"
Net Volume	12 cu. ft.
Unit Weight	214 lb.
Shipping Weight	275 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	2.7
Plug Type	NEMA 5-15P
Power Cord Length	84"

COOLING


Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/5

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 20.8"W x 17.1"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Interior Light	No
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: UC-48R



NEMA 5-15P

