

Solid Dual Temperature

Reach-In Top Mount
J Series

FEATURES & BENEFITS

Model : JRF-19

Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures.
- Alarms that sound when doors are not sealed shut; protect against food spoilage that originate from cold air leaks.
- Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- Rapid cool-down function (Turbo freeze).
- Smart fuzzy defrost system.
- Automatic evaporator fan motor delays.

Hot gas condensate system Only Turbo Air models

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

Door pressure release device Only Turbo Air models

Pressure relief doors are designed to eliminates vacuum pressure and allows easy, instant door opening.

Efficient refrigeration system

Turbo Air's J series dual temp. models are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

Exterior & interior of cabinet construction

Stainless steel exterior (galvanized steel top, bottom and back) and stainless steel interior with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury.

Left hinged model available

Adjustable, heavy duty, PE(polyethylene) coated wire shelves

LED interior lighting

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Refrigerator holds 33°F ~ 38°F, and freezer holds -10°F ~ 0°F for the best in food preservation



ENERGY STAR®
Qualified

Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D* x H [†] (inches)
JRF-19	2	9.1(F)/9.1(R)	2	3/4	5	220	251/8 x 311/2 x 72

Solid Dual Temperature

Reach-In Top Mount
J Series

Model : JRF-19

ELECTRICAL DATA

Voltage	115/60/1
Plug Type	① NEMA 5-15P
Full Load Amperes	5
Compressor HP	3/4
Feed Wires with Ground	3
Cord Length (ft.)	9
Refrigerant	R-404A

DIMENSIONAL DATA

# of Doors	2
Net Capacity (cu. ft.)	9.1(F)/9.1(R)
Ext. Length Overall (in.)	25 1/8 (640mm)
Ext. Depth Overall (in.) *	31 1/2 (800mm)
Ext. Height Overall (in.) †	72 (1829mm)
Freezer Int. Demension (L x D x H) (in.)	21 5/8 x 25 3/8 x 26 3/4
Ref. Int. Demension (L x D x H) (in.)	21 5/8 x 25 3/8 x 28 7/8
Gross Weight (lbs.)	210
Net Weight (lbs.)	220
# of Shelves	2
Shelf Size (in.)	20 1/2 x 23 5/8

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for rear condensate enclosure.

† Height does not include 5" for caster height.

■ WARRANTY : 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor


- **Door locks standard**
- **Self-contained system**
- **Standard 4" dia. swivel casters with locks on the front set**
- **Solid and sturdy grille design**
- **Legs available (optional)**

■ OPTIONAL ACCESSORIES :


- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake),
M726500200 (w/ brake)
- 6" stainless steel leg: 30221M0600
- Additional PE coated wire shelf: K1F9000103

PLAN VIEW


(unit : inch)



FRONT VIEW



TOP VIEW



SIDE VIEW

Ver.201601

- Turbo Air : 800-627-0032 ■ GK : 800-500-3519
- Warranty : 800-381-7770 ■ AC : 888-900-1002



ENERGY STAR®
Qualified

Turbo air REFRIGERATOR MANUFACTURER

GERMAN KNIFE

RADIANCE

GREEN WORLD

Turbo air AIR CONDITIONER MANUFACTURER