

ADVANTEDGE™ DIRECT DRAW BEER COOLERS



NLDD59

PROJECT:

ITEM NUMBER:

MODEL NUMBER:

DIRECT DRAW BEER COOLERS

SPECIFICATIONS FOR: NLDD24, NLDD59, NLDD69, NLDD79, NLDD95


- Finish: Heavy duty stainless steel top, black front, sides and back. Galvanized steel interior walls with stainless steel floor.
- Insulation: Foamed-in-place 1-1/2" CFC free polyurethane insulation
- Hardware: Solid doors with locks, magnetic door gaskets, plastic breaker strips around door openings to limit the formation of any condensation. Interior LED light (except NLDD24). 3" diameter stainless steel draft towers. Heavy duty stainless steel threshold. Casters standard on NLDD24 model only.
- Electrical: 115 volt, 60 Hz, 1 phase with cord and NEMA 5-15P plug
- Refrigeration: Self-contained forced air R290 capillary tube refrigeration system. Temperature range from +34°F to +38°F. Draft towers cooled by continuous cold air circulation. Adjustable temperature control.
- Approvals: ETL Sanitation listed, UL, C-UL Safety listed, approved to NSF standard for packaged food products **

STANDARD FEATURES


- Adjustable temperature control
- Black front, sides and back
- Free flowing refrigeration system at all times to ensure uniformly cooled product
- LED interior light (except NLDD24)
- 5" casters standard on NLDD24 model only
- 3" diameter polished stainless steel draft tower
- 1 two-way gas manifold (NLDD59 & NLDD69), 1 three-way gas manifold (NLDD79), 1 four-way gas manifold (NLDD95)
- Slide out condensing unit
- Temperature range: +34°F to +38°F
- ETL Sanitation listed, UL, C-UL Safety listed, approved to NSF standard for packaged food products **
- Warranties: 3 year parts & labor, 5 year compressor

OPTIONAL FEATURES *


- 4" plate-mounted casters
- Floor rack
- Single, double and triple tap draft tower




TOP
NLDD59




TOP
NLDD24




FRONT
NLDD24




SIDE
NLDD24




SIDE
NLDD59, 69, 79, 95




FRONT
NLDD59




TOP
NLDD69



FRONT
NLDD69



TOP
NLDD79




FRONT
NLDD79


Models	NLDD24	NLDD59	NLDD69	NLDD79	NLDD95
<i>Crated Weight (lbs) (kg)</i>	187 (85)	276 (125)	298 (135)	400 (182)	460 (209)
<i>Crated Height (in) (cm)</i>	44 (112)	44 (112)	44 (112)	44 (112)	44 (112)
<i>Crated Width (in) (cm)</i>	27-1/2 (70)	61-1/2 (156)	71-1/4 (181)	82-5/8 (210)	97-5/8 (248)
<i>Crated Depth (in) (cm)</i>	30 (76)	30 (76)	30 (76)	30 (76)	30 (76)
<i>Interior Height (in) (cm)</i>	31-3/4 (81)	31-3/4 (81)	31-3/4 (81)	31-3/4 (81)	31-3/4 (81)
<i>Interior Width (in) (cm)</i>	19-3/8 (49)	54-3/4 (139)	64-3/4 (165)	76-1/2 (194)	91 (231)
<i>Interior Depth (in) (cm)</i>	24 (61)	21-3/8 (54)	21-3/8 (54)	21-3/8 (54)	21-3/8 (54)
<i>Overall Height (in) (cm)</i>	39-1/4 (100)	37 (94)	37 (94)	37 (94)	37 (94)
<i>Overall Width (in) (cm)</i>	23-3/8 (59)	59 (150)	69-1/8 (176)	80-3/4 (205)	95-1/4 (242)
<i>Overall Depth (in) (cm)</i>	30-3/4 (78)	29-5/8 (75)	29-5/8 (75)	29-5/8 (75)	29-5/8 (75)
<i>Gross Cubage (CuFt) (L)</i>	7.9 (223.7)	19.4 (549.3)	23.4 (662.6)	27.9 (790)	33.6 (951.4)
<i>Number of Towers</i>	1 single	2 single	2 single	1 single 1 double	2 double
<i>Number of Kegs</i>	1	2**	3	4	5
<i>Condensing Unit Size</i>	1/5 HP	3/8 HP	3/8 HP	3/8 HP	3/8 HP
<i>Refrigerant</i>	R290	R290	R290	R290	R290
<i>Electrical Characteristics</i>	115/60/1	115/60/1	115/60/1	115/60/1	115/60/1
<i>Cord and Plug Furnished</i>	Yes	Yes	Yes	Yes	Yes
<i>NEMA Plug Configuration</i>	5-15P	5-15P	5-15P	5-15P	5-15P
<i>Total Amp Draw</i>	3.0	3.5	3.5	3.5	3.5

Specifications subject to change without notice.

** The NLDD59 will hold (2) 1/2 barrel kegs and (1) slim quarter barrel.



TOP
NLDD95



FRONT
NLDD95



NORLAKE

Revision Date: 1/19
Part Number: 143585

Standex
Food Service Equipment Group

©2019 Nor-Lake, Inc. A division of Standex International Corp. All rights reserved.
Printed in the USA.